

**Small Mounting Flange FS**

SMALL MOUNTING FLANGE Material - aluminum, brass, or stainless steel (see Appendix - Sheath materials) Application - with TS, LC, and RH probes	DIMENSIONS	NOMINAL SIZE *									
		DN5	DN6	DN8	DN9	DN10	DN12	DN14	DN16	DN18	
	<i>d1 (probe OD) [mm]</i>	5	6	8	9	10	12	14	16	18	
	<i>D [mm]</i>	32	34	40	40	42	44	46	48	50	
	<i>b [mm]</i>	2 (stainless steel), 3 (brass), or 4 (aluminum)									
	<i>k [mm]</i>	24	26	30	30	32	34	36	38	40	
	<i>d3 [mm]</i>	13	14	18	19	20	22	24	26	28	
	<i>h1 [mm]</i>	14	14	16	16	16	16	16	18	18	
	<i>no. of bolts</i>	2	2	3	3	4	4	4	4	4	
	<b>Fixing:</b> stainless steel screw M4										
	<b>Maximum temperature:</b> 300 °C										
	<b>Maximum pressure:</b> atmosphere										
* Other dimensions are available on request. Please contact COMECO!											

**Ordering code** FS - G4.G10

Code	Feature or option	Code values
G4	Nominal size	DN5, DN6, DN8, DN9, DN10, DN12, DN14, DN16, DN18, Z - other (specify!)
G10	Material	AL - aluminum, BR - brass (Ni-plated) <sup>(1)</sup> , M1 - 1.4301, M2 - 1.4541 <sup>(1)</sup> , M3 - 1.4571 <sup>(1)</sup> , M9 - 1.4404

<sup>(1)</sup> Contact COMECO!